


CONSTRUCTION IN CURB LANE OF A TWO-WAY TWO LANE ROADWAY WITH A COMMON LEFT TURN LANE

## NOTES:


- 1. DETOUR ROUTE TO BE PROTECTED BY TEMPORARY STOP SIGNS FOR MAJOR STREET.
- 2. PARKING TO BE PROHIBITED ON DETOUR ROUTE AS REQUIRED
- 3. ADDITIONAL SIGNING MAY BE REQUIRED ON LONGER DETOUR ROUTES.
- 4. AS DIRECTED BY THE DIRECTOR OF PUBLIC WORKS AND UTILITIES, PERMANENT STRIPING TO BE REMOVED AND TEMPORARY STRIPING INSTALLED.
- 5. WHEN CONSTRUCTION IS COMPLETED, TEMPORARY STRIPING IS TO BE REMOVED AND PERMANENT STRIPING INSTALLED BY OTHERS.

THE CONTRACTOR SHALL MAINTAIN TRAFFIC DURING CONSTRUCTION AND PROVIDE, INSTALL, MAINTAIN AND REMOVE ALL TRAFFIC CONTROL DEVICES IN ACCORDANCE WITH THE CITY OF LINCOLN STANDARD SPECIFICATIONS, THE PROJECT SPECIAL PROVISIONS, THE CITY OF LINCOLN TRAFFIC CONTROL GUIDELINES FOR STREET CONSTRUCTION, MAINTENANCE AND UTILITY OPERATIONS, THE ORDINANCES AND REGULATIONS OF THE CITY OF LINCOLN AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES. FAILURE OF THE CONTRACTOR TO ERECT AND MAINTAIN APPROVED TRAFFIC CONTROL DEVICES SHALL BE REASON TO SUSPEND THE WORK.




CONSTRUCTION IN CURB LANE ADJACENT TO LEFT

TURN LANE, OPPOSING DIRECTION.



TWO-WAY TWO LANE NON-RESIDENTIAL FLAGGER OPERATION, NO LONGER THAN ONE (1) NORMAL WORKING DAY OR EMERGENCY WORK



(15)

(16)

(17)

DETOUR



KEEP FIGHT


(11)

DETOUR AHEAD

(10)


ROAD CLOSED


(12)



## FORMULA FOR TAPER LENGTH

- L = S x W FOR SPEEDS OF 45 MPH OR OVER
- $L = \frac{W \times S^2}{60}$  FOR SPEEDS OF 40 MPH OR UNDER
- L = LENGTH OF TAPER
- W = WIDTH OF LANE





REDUCED

SPEED

AHEAD

(20)

DO NOT ENTER

(18)

(19)

FINES DOUBLED

FOR SPEEDING

IN WORK ZONES

(21)

WORK ZONE TRAFFIC CONTROL L.S.P. 99